

General Data

STARTER

Type	M35G	M35J
Lock torque	7.7 lb/ft (1.06 kgm.)	7.0 lb/ft. (0.97 kgm.)
@ amps	330-350	350-370
Light running current	60 amps.	65 amps.
@ r.p.m.	5,500/6,000	8,000/10,000
Minimum brush length	$\frac{5}{16}$ in. (7.9 mm.)	$\frac{3}{8}$ in. (9.5 mm.)
Brush spring tension—new	30-34 oz. (850-910 gm.)	28 oz. (800 gm.)
Minimum with worn brushes	25 oz. (711 gm.)	with new brush protruding $\frac{1}{16}$ in. (1.5 mm.) from brush box

LIGHTING

System	Earth return
Type—Headlamp (all models except Stiletto)	F.700 Mk. 10
—(Stiletto)	Dual F.575
—Side and front flasher lamp	Lucas 717
—Rear number plate lamp	Lucas 719
—Stop/tail lamp	Lucas 692
—Rear flasher lamp	Lucas 691

LAMP BULBS AND LIGHT UNITS

Head (R.H.D. and Stiletto L.H.D. inner)... ..	Sealed beam unit
Head (L.H.D. including Stiletto outer)	Bulb 410 12v 45/40w
Head (France including Stiletto inner and outer)	Bulb 411 12v 45/40w
Head (N. America)	Light unit (7105078) Sealed beam unit
Side	989 12v. 6w. or 222 12v. 4w.
Stop and tail	380 12v. 21/6w.
Front and rear flashing indicator	382 12v. 21w.
Rear number plate	207 12v. 6w.
Interior	254 12v. 6w. (festoon)
Panel	987 12v. 2.2w.
Headlamp main beam indicator	987 12v. 2.2w.
Ignition warning	987 12v. 2.2w.
Flashing indicator warning	987 12v. 2.2w.
Oil pressure warning	987 12v. 2.2w.

OTHER ELECTRICAL EQUIPMENT

Windscreen wiper—Make	Lucas
—Type	DR.3A (Saloon and Van)
	12WA (Coupe and Sport Saloon, early)
	14W (Coupe and Sport Saloon, late, California and Stiletto)
—Armature end play012/.008 in. (.3/.2 mm.)
Horns—Make and type	Lucas 9H or 6H or Clear Hooter F725